



UNTREATED

TREATED

ANTI-MICROBIAL NANO-CERAMIC COATING

Glidecoat's Anti-Microbial Nano-Ceramic Coating has been designed for use underwater. It can be used as a replacement for bottom paint, whether on paint or gelcoat.

If bottom paint exists it must be removed prior to application, by sand or soda blasting.

Developed as a 9H ceramic coating, the product contains an anti-microbial which deters marine growth, beyond those benefits found with ceramic coatings, which produce a hydrophobic surface, eliminating pores in the surface which marine life can adhere to.

Note: Before applying, ensure the surface has been fully prepped, including cleaning, removal of any marine organisms, dirt, salt scum or other surface contaminants to ensure a consistent surface. Prior to coating, wipe down the surface with Glidecoat Surface Wipe or De-Natured Alcohol.

This product should not be applied over boat paint, but should be applied directly to paint or gelcoat.

For technical questions or any challenges with the preparation or application process please call 561-290-0165. Ext. 2 for Dealer Support.

For safety and disposal information visit www.glidecoat.com.

APPLICATION INSTRUCTIONS

Start by mixing Part B bottle into Part A bottle. The mix ratio has been pre-measured at 30/70, so there is nothing to measure simply mix the B bottle into the A Bottle. Shake well after mixing and use the mixed product within 7-10 days. Do not leave the bottle open or exposed to air as the humidity in the air, will cause the product to cure.

1. Apply a small amount of Glidecoat Anti-Microbial Nano-Ceramic Coating to the application pad. Use light to medium pressure to a small area 2' x 2'. Make sure the entire area is covered and appears wet.
2. Using a clean white microfiber towel to lightly buff area coated to achieve a smooth shiny surface. Remove all liquid before proceeding to next step. When proceeding to new sections, be sure to overlap ensuring area is covered entirely
4. Once complete with this step, make sure all areas are uniform. We suggest you apply 3-4 coats. The following coats can be applied when the surface is finger touch dry from the previous coat
5. To completely cure after the coats have been applied, allow 24 hours before washing or splashing the boat. When coating, the area should be well ventilated, not in direct sun light, and avoid contact of products on your skin. For safety and disposal information visit www.glidecoat.com.

DISCLAIMER:

Glidecoat a division of Onan Technologies Inc.'s maximum liability for or with respect to any damages of any kind to any person, property or otherwise, caused to any Customer or any other person as a result of or with respect to any proven breach of any express or implied warranty with respect to any Product; misrepresentation with respect to any Product; Product error, failure or malfunction; formula, engineering or design error; manufacturing or packaging error; labelling error; Product failure to perform; or any other act or omission of any kind whatsoever with respect to any Product, shall be limited the price paid by the Customer for the Product at the time of original purchase (not including shipping, handling, sales taxes or installation services); and Product purchase price refund shall be Customer's only claim or remedy arising therefrom. IN ADDITION TO AND WITHOUT LIMITATION OF THE FOREGOING, GLIDECOAT SHALL NOT BE LIABLE UNDER ANY RULE OR THEORY OF LAW TO ANY CUSTOMER OR ANY OTHER PERSON FOR (A) INCIDENTAL, CONSEQUENTIAL, SPECIAL, PUNITIVE, OR EXEMPLARY DAMAGES OF ANY KIND, INCLUDING BUT NOT LIMITED TO LOSS OF REVENUES, LOSS OF PROFITS, LOSS OF BUSINESS, OR OTHER ECONOMIC DAMAGES, OR (B) ERRORS MADE IN THE HANDLING, STORAGE OR INSTALLATION OR APPLICATION OF ANY PRODUCT, REGARDLESS OF WHETHER ONAN WAS ADVISED OF, KNEW OR OUGHT TO HAVE KNOWN OF THE POSSIBILITY OR RISK OF SUCH LOSSES OR DAMAGES.

GLIDECOAT